

**HAZARD RATING**

4=EXTREME  
 3=HIGH  
 2=MODERATE  
 1=SLIGHT  
 0=INSIGNIFICANT

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>REACTIVITY</b>	<b>0</b>

**MATERIAL SAFETY DATA SHEET**  
**VEXCON NO. CP116B**



**Performance Construction Chemicals**

7240 STATE RD • PHILADELPHIA, PA 19135

VOICE: 215.332.7709 • FAX: 215.332.9997

TOLL FREE: 888-VEXCON-1

WEBSITE ADDRESS: [www.vexcon.com](http://www.vexcon.com)

**GENERAL INFORMATION**

**PRODUCT IDENTIFICATION:** MOISTUREBLOC™ MOISTURE REDUCTION

TOPCOAT STEP 2 LOW ODOR

**VOC CONTENT:** 671 GRAMS/LITER OR 5.60 #/GAL.

**CATEGORY:** CURE AND SEAL

**COMMON NAME:** STYRENE ACRYLATE COPOLYMER IN AROMATIC/  
 ALIPHATIC SOLVENT

**DOT SHIPPING NAME:** IN CONTAINER LESS THAN 119 GALS:  
 MOISTUREBLOC ADHESIVE TOPCOAT STEP 2 (NON-REGULATED)  
 IN CONTAINERS GREATER THAN 119 GALS: COMBUSTIBLE  
 LIQUID, N.O.S. (AROMATIC SOLVENT), 3, NA 1993, III  
**FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:** RQ (ACETONE)  
 RESIN SOLUTION, FLAMMABLE, 3, UN1866, III

**HEALTH AND SAFETY** COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE  
 VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: (USE OF  
 SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE  
 EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT:) ASPIRATION OF  
 MATERIALS INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONIA WHICH  
 CAN BE FATAL USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN  
 CONFINED AREA.

**SECTION I**

**MANUFACTURER:** VEXCON CHEMICALS  
**EMERGENCY NO:** 1-800-858-2828  
**CHEMTREC NO:** 1-800-424-9300  
**TELEPHONE NO:** 1-215-332-7709  
**ADDRESS:** 7240 STATE RD., PHILA., PA 19135  
**PREPARED:** SEPTEMBER 2000  
**UPDATED:** JANUARY 2006  
**PREPARED BY:** DARRYL F. MANUEL

**SECTION II HAZARDOUS INGREDIENTS**

<b>MATERIAL OR COMPONENTS</b>	<b>CAS. NO</b>	<b>%</b>	<b>HAZARD DATA</b>	<b>UN#</b>
STYRENE ACRYLATE POLYMER	25036-16-2	14-30%	ND	
AR 100 SOLVENT	64742-95-6	25%	TLV 50 PPM OSHA HAZARD: COMBUSTIBLE	1268
WHICH CONTAINS HYDROCARBONS			OSHA PEL: ACGIH TLV	
TRIMETHYLBENZENE			OSHA PEL: ACGIH TLV	
STODDARD SOLVENT	8052-41-3	66-40%	TLV 100 PPM	1255

**THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE**

**INGREDIENTS:**

<b>COMPONENT</b>	<b>MAXIMUM %</b>	<b>CAS NO</b>
TRIMETHYLBENZENE	10	95-63-6

**SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS**

**BOILING POINT:** 310-405 F      **MELTING POINT:** N/A  
**SPECIFIC GRAVITY (H2O=1)** 0.870      **VAPOR PRESSURE:** 3.1 mm Hg @20C  
**VAPOR DENSITY (AIR=1):** 4.9  
 PH (AS IS): NA      PH (1% SOLN): NA  
**SOLUBILITY IN H2O % BY WT:** INSOLUBLE      **% VOLATILES BY VOL:** 70-86%  
**EVAPORATION RATE (BUOH=1):** 0.12

**APPEARANCE AND ODOR:** WATER WHITE LIQUID WITH PAINT SOLVENT  
 ODOR.(MAY CONTAIN FUGITIVE RED DYE).

**SECTION IV FIRE AND EXPLOSION DATA**

**FLASH POINT:** (TEST METHOD): 106 F TCC  
**AUTOIGNITION TEMPERATURE:** 473  
**FLAMMABLE LIMITS IN AIR: % BY VOL:** ND  
**LOWER:** 0.5      **UPPER:** 6.0

**EXTINGUISHING MEDIA:** REGULAR FOAM, CARBON DIOXIDE OR  
 DRY CHEMICAL. WATER MAY BE USED TO REDUCE THE RATE OF  
 BURNING AND FOR COOLING PURPOSES.

**GENERAL HAZARD:** COMBUSTIBLE LIQUID, CAN FORM COMBUSTIBLE  
 MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC  
 DISCHARGE, MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH  
 CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY"  
 CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND  
 CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT WELD, BRAZE,  
 SOLDER DRILL GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT,  
 FLAME, SPARKS, STATIC ELECTRICITY OR OTHER SOURCES OF  
 IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY  
 DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND  
 PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY  
 DISPOSED OF.

**SPECIAL FIRE FIGHTING PROCEDURES:** THE USE OF SELF-CONTAINED  
 BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN  
 PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. UNUSUAL  
 FIRE AND EXPLOSION HAZARD: VAPOR IS HEAVIER THAN AIR AND MAY  
 TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM  
 CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH  
 BACK.

## SECTION V REACTIVITY DATA

**CONDITIONS CONTRIBUTING TO INSTABILITY:** PRODUCT IS STABLE.  
**INCOMPATIBILITY:** THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS STRONG ACIDS OR BASES AND SELECTED AMINES.  
**HAZARDOUS DECOMPOSITION PRODUCT:** THERMAL DECOMPOSITION IN THE PRESENCE OF AIR YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.  
**CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

## SECTION VI HEALTH HAZARD INFORMATION

### HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

**ROUTES OR EXPOSURE/INHALATION:** THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION.  
AR 100 COMPONENT AND STODDARD SOLVENT  
**SKIN CONTACT:** THIS PRODUCT MAY RESULT IN SKIN IRRITATION UPON PROLONGED/REPEATED CONTACT.  
AR 100 COMPONENT AND STODDARD SOLVENT  
**SKIN ABSORPTION:** SEE ABOVE

**EYE CONTACT:** THIS PRODUCT MAY BE AN EYE IRRITANT.  
AR 100 COMPONENT AND STODDARD SOLVENT  
**INGESTION:** SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.  
**EFFECTS OF OVEREXPOSURE TLV-50 ppm**

**ACUTE OVEREXPOSURE: ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS:** MODERATE IRRITATION BY LIQUID TO SKIN AND EYES.

### EMERGENCY AND FIRST AID PROCEDURES:

**EYES:** FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.  
**SKIN:** WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.  
**INHALATION:** MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.  
**INGESTION:** DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

## SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE AND SPILL CONTROL

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROL CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTS NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.  
**WATER SPILL:** REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSENTS MAY BE USED IN ON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

## SECTION VIII CONTROL MEASURES

**VENTILATION REQUIREMENTS:** LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF GENERAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

**RESPIRATORY (SPECIFY IN DETAIL):** THE USE OF RESPIRATORY

PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF A OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIRPACK.  
**EYE:** CHEMICAL GOGGLES AND/OR FACE SHIELDS ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.  
**GLOVES:** THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS.  
**OTHER CLOTHING AND EQUIPMENT:** IMPERMEABLE APRONS AND HELMETS (HEAD COVER) ARE ADVISED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYEWASHES AND SAFETY SHOWERS IN WORK AREAS ARE RECOMMENDED.

## SECTION IX SPECIAL PRECAUTIONS

### PRECAUTIONARY STATEMENTS:

**FIRE FIGHTING: WATER** MAY BE UNSUITABLE AS AN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE REMOVE SATURATED CLOTHING AND FLUSH AFFECTED AREAS WITH WATER.

### OTHER HANDLING AND STORAGE REQUIREMENTS:

KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR.

**HMS HAZARD RATINGS:** THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS

	NPCA-HMS	NFPA 704	KEY
HEALTH	2	2	4=SEVERE
FLAMMABILITY	2	2	3=SERIOUS
REACTIVITY	0	0	2=MODERATE 1=SLIGHT 0=MINIMAL

## SECTION X REGULATORY INFORMATION

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6.

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 800-424-8802. THE REPORTABLE SPILL QUANTITY OF THIS PRODUCT IS 5,000 POUNDS.

**THIS PRODUCT CONTAINS: XYLENE, ETHYLBENZENE, CUMENE, and TRIMETHYLBENZENE**

**SARA TITLE III: UNDER** THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES.

### DELAYED HEALTH, FIRE,

FEDERAL:

FDA:

USDA:

TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

**PREPARED BY:** DARRYL MANUEL  
**TITLE:** PRESIDENT  
**COMPANY:** VEXCON CHEMICALS,  
7240 STATE ROAD,  
PHILA., PA 19135

**THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN**