



# PRODUCT SPECIFICATIONS

## ROCKIES - SPC

### PRODUCT INFORMATION

<b>Line</b>	Rockies
<b>Construction</b>	4 mm SPC, 1 mm EVA
<b>Thickness</b>	5 mm (0.5 mm W/L)
<b>Finish</b>	Ceramic Bead Coating
<b>Installation</b>	Drop Loc

### PRODUCT PACKAGING

<b>Size</b>	1220 mm x 182 mm (48 in. x 7 in.)
<b>Pcs/Carton</b>	10
<b>Weight/Carton</b>	18.3 kg (40.3 lbs.)

### TESTING

Performance	Test Method	Requirement	Performance vs. Requirement
Residual Indentation	ASTM F1914	Average residual indentation ≤ 8% Max residual indentation ≤ 10%	Meets
Static Load Limit @ 250 psi	ASTM F970	Residual Indentation ≤ 4%	Meets
Dimensional Stability	ASTM F3261-17 Section 8.3 and ISO 23999	≤ 0.2%/305mm	Meets
Curling	ASTM F3261-17 Section 8.3 and ISO 23999	≤ 2 mm	Meets
Chemical Resistance	ASTM F925	No more than slight change in surface dulling, attack or staining	Meets
Resistance to Heat	ASTM F1514	ΔE not greater than 8.0	Meets
Average Hardness	ASTM D1037	N/A	Front View = 11,659 N Back View = 11,710 N
Phthalate Content	CPSC-CS-C1001-09.3	N/A	Not detected
Soluble Elements	ASTM F963	N/A	Not detected
Static Coefficient of Friction	ASTM D2047	N/A	Dry: 0.43 Wet: 0.62
Peel Strength	ASTM D903	N/A	Mean = 0.34 kg/mm Max = 0.35 kg/mm Min = 0.32 kg/mm
Impact Insulation Class (IIC)	ASTM E492	N/A	Calculated IIC = 65
Sounds Transmission Class (STC)	ASTM E90	N/A	Calculated STC = 63

### LIMITED WARRANTY

As on Quickstyle website

